

WHAT IS CLAIMED IS:

1. A vibration type actuator comprising:

an elastic member in which a shaft center portion
is formed in hollow shape along an axial direction and
in which driving vibration is generated in a driving
portion;

a fastening member which fastens said elastic
member to an electro-mechanical energy conversion
element;

an output shaft which penetrates the shaft center
portion of said elastic member;

a moving member which is kept in press contact
with the driving portion of said elastic member and
which rotates together with said output shaft; and

a bearing member which is located on an inner
periphery portion of said bearing member and near a
distal end portion of said fastening member and which
journals said output shaft.

2. A vibration type actuator according to Claim
1, wherein said bearing member has one surface facing
the distal end portion of said fastening member and
another surface opposite thereto facing said elastic
member.

3. A vibration type actuator according to Claim
1, wherein said bearing member can move by a fixed

distance along said axial direction.

4. A vibration type actuator according to Claim
1, wherein said elastic member has a clearance in which
5 said bearing portion can move in the axial direction,
near the distal end portion of said fastening member.

5. A vibration type actuator according to Claim
1, wherein said output shaft is restrained from
10 slipping off outward in the axial direction.

6. A vibration type actuator according to Claim
1, wherein said fastening member is a hollow thread
member which has a thread portion formed in an outer
15 periphery portion and wherein said elastic member has a
step which restrains a screwing position of said
fastening member, in the inner periphery portion
thereof.

7. A vibration type actuator according to Claim
1, wherein said bearing member is deformable in a
20 direction of a shaft center of said output shaft.

8. A vibration type actuator according to Claim
1, wherein said bearing member is deformable in the
25 axial direction of said output shaft.

105250" 59249360

5

10

15

20

25

14. A vibration type actuator comprising:
a plurality of elastic members in each of which a shaft center portion is formed in hollow shape along an axial direction and in each of which driving vibration

is generated in a driving portion;

an electro-mechanical energy conversion element which is interposed between said plurality of elastic members;

5 a fastening member in which a shaft center portion is formed in hollow shape along an axial direction and which fastens said elastic members to said electro-mechanical energy conversion element;

10 an output shaft which penetrates the shaft center portions of said elastic members and which is restrained from slipping off outward in an axial direction;

15 a moving member which kept in press contact with the driving portion of said elastic members and which rotates together with said output shaft; and

20 a bearing portion which is located on an inner periphery portion of said elastic members and near a distal end portion of said fastening member and which journals said output shaft.

25 15. A vibration type actuator according to Claim 14, wherein said bearing portion has one surface facing the distal end portion of said fastening member and another surface opposite thereto facing said elastic member.

16. A vibration type actuator according to Claim

14, wherein said bearing portion can move by a fixed distance along said axial direction.

17. A vibration type actuator according to Claim
5 14, wherein said elastic member has a clearance in which said bearing portion can move in the axial direction, near the distal end portion of said fastening member.

10 18. A vibration type actuator according to Claim 14, wherein a moving distance of said bearing portion in said axial direction is restrained by the inner periphery portion of said elastic members and the
15 distal end portion of said fastening member.

095465 05201
T05250" 59249860